

SAFETY DATA SHEET

Date Prepared : 11/28/2017
MSDS No : JSP-0290 Aerosol
Date Revised : 11/28/2017
Revision No : 12

STA'-PUT S200 Aerosol Adhesive

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: STA'-PUT S200 Aerosol Adhesive

MANUFACTURER

ITW Polymers Sealants North America
 56 Air Station Industrial Park
 Rockland, MA 02370

Product Stewardship: (781) 878-7015

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300

COMMENTS: STA'-PUT is a registered trademark of Illinois Tool Works, Inc.

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Irritation, Category 2
 Eye Irritation, Category 2A
 Carcinogenicity, Category 2
 Target Organ Toxicity (Single exposure), Category 3
 Target Organ Toxicity (Repeated exposure), Category 2

Physical:

Liquefied Gases
 Flammable Liquids, Category 1

GHS LABEL



Health hazard



Flame



Exclamation mark



Gas cylinder

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H224: Extremely flammable liquid and vapour.
 H280: Contains gas under pressure; may explode if heated.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H335: May cause respiratory irritation.
 H336: May cause drowsiness or dizziness.
 H351: Suspected of causing cancer.
 H373: May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENT(S)

Prevention:

[201]: Obtain special instructions before use.
 P202: Do not handle until all safety precautions have been read and understood.
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

SAFETY DATA SHEET

Date Prepared : 11/28/2017
MSDS No : JSP-0290 Aerosol
Date Revised : 11/28/2017
Revision No : 12

STA'-PUT S200 Aerosol Adhesive

P260: Do not breathe dust/fume/gas/mist/vapours/spray.
 P264: Wash thoroughly after handling.
 P271: Use only outdoors or in a well-ventilated area.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P302+P352: IF ON SKIN: Wash with plenty of water.
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313: IF exposed or concerned: Get medical advice/ attention.
 P321: Specific treatment is required.
 P332+P313: If skin irritation occurs: Get medical advice/attention.
 P337+P313: If eye irritation persists: Get medical advice/attention.
 P362: Take off contaminated clothing.
 P381: In case of leakage, eliminate all ignition sources.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.
 P405: Store locked up.
 P410: Protect from sunlight.

Disposal:

P501: Dispose of contents/container according to local, regional, national, and international regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Contains methylene chloride which is a nonflammable liquid with a mildly sweet odor.

IMMEDIATE CONCERNS: DANGER! Poison. Extremely flammable vapor. Vapors may cause flash fire and explosion. Contents under pressure. Harmful or fatal if swallowed. Vapors may cause dizziness, headache, nausea, drowsiness, unconsciousness and respiratory irritation. Contains methylene chloride which is harmful if inhaled. Can also cause skin and eye irritation. Methylene Chloride is a possible cancer hazard. May cause cancer based on animal data.

POTENTIAL HEALTH EFFECTS

EYES: Can cause moderate to severe eye irritation with temporary damage possible.

SKIN: Prolonged or repeated contact of liquid can cause irritation, defatting of skin, and dermatitis. Prolonged single exposure can result in a progressively severe burning sensation or redness.

SKIN ABSORPTION: Can be absorbed through the skin but not in sufficient amounts to cause adverse effects.

INGESTION: Harmful or fatal if swallowed. Can cause gastrointestinal irritation with symptoms of nausea, vomiting and diarrhea.

INHALATION: Inhalation is the major potential route of exposure. Exposure to high concentrations of vapor or mist can cause central nervous system depression with symptoms of headache, dizziness, stupor, loss of consciousness or death depending on concentration and duration of exposure. Exposure to high concentrations can cause irregular heartbeat, cardiac arrest and death. Overexposure has been shown to cause adverse effects on the lungs, liver, kidney, nervous system and internal organs. Carboxyhemoglobin levels can be elevated in persons exposed to methylene chloride and can cause a substantial stress on the cardiovascular system.

REPRODUCTIVE TOXICITY

REPRODUCTIVE EFFECTS: Methylene chloride has been evaluated for its potential to induce genotoxic effects

SAFETY DATA SHEET

Date Prepared : 11/28/2017
MSDS No : JSP-0290 Aerosol
Date Revised : 11/28/2017
Revision No : 12

STA'-PUT S200 Aerosol Adhesive

in both in vivo and in vitro systems with mixed results. Based on this evidence, methylene chloride exposure may be considered to be a weak mutagen in mammalian systems.

TERATOGENIC EFFECTS: None known.

CARCINOGENICITY: Methylene chloride has caused cancer in certain laboratory animal tests. IARC has classified methylene chloride in Group 2B as a substance considered possibly carcinogenic to humans. Methylene chloride appears on the NTP carcinogen list.

MUTAGENICITY: None known.

ROUTES OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, and Skin Contact

TARGET ORGAN STATEMENT: Central Nervous System (CNS)

CANCER STATEMENT: Methylene chloride has caused cancer in certain laboratory animal tests. IARC has classified methylene chloride in Group 2B as a substance considered possibly carcinogenic to humans. Methylene chloride appears on the NTP carcinogen list.

IRRITANCY: Eyes, nose, throat, respiratory tract, and skin irritation.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Methylene Chloride	45 - 70	75-09-2
Hydrocarbon Propellant	25 - 50	Mixture

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of tempered water (at least 15-20 minutes) lifting upper and lower eye lids occasionally. Get immediate medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash or dispose of clothing before reuse.

INGESTION: Do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes eye irritation.

SKIN: Mild to moderate skin irritant.

SKIN ABSORPTION: Can be absorbed through the skin but not in sufficient amounts to cause adverse effects.

INGESTION: Ingestion of this material can cause mouth, throat, esophageal, and gastrointestinal tract irritation.

INHALATION: Exposure to high concentrations of vapor or mist can cause central nervous system depression with symptoms of headache, dizziness, stupor, loss of consciousness or death depending on concentration and duration of exposure. Exposure to high concentrations can cause irregular heartbeat, cardiac arrest and death. Overexposure has been shown to cause adverse effects on the lungs, liver, kidney, nervous system and internal organs.

CHRONIC EFFECTS: Prolonged overexposure has caused toxic effects on the liver and kidneys.

SAFETY DATA SHEET

Date Prepared : 11/28/2017
MSDS No : JSP-0290 Aerosol
Date Revised : 11/28/2017
Revision No : 12

STA'-PUT S200 Aerosol Adhesive

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Class IA

GENERAL HAZARD: Extremely Flammable. Under Pressure.

EXTINGUISHING MEDIA: Foam, dry chemical, carbon dioxide, water spray or fog.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide, Carbon Dioxide, Aldehydes

EXPLOSION HAZARDS: Avoid fire, sparks, static electricity and hot surfaces. Liquid readily evaporates at room/ambient temperature. Vapors are invisible, flammable, heavier than air, and may accumulate in low areas and spread long distances. Distant ignition and flashback are possible.

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus with pressure-demand, full face piece SCBA (MSHA/NIOSH approved or equivalent) and full protective gear.

SENSITIVE TO STATIC DISCHARGE: Likely to catch fire from near-by spark. Static charge may accumulate by flow or agitation. Grounding and bonding of containers is required.

SENSITIVITY TO IMPACT: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide and Carbon Dioxide may form when heated to decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed, thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.

LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof mechanical means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. Flammable vapors may cause flash fire or ignite explosively. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near container. Do not cut, drill, grind, or expose containers to heat, sparks, static electricity or other source of ignition. Explosion may occur causing injury or death.

HANDLING: Use adequate ventilation and appropriate respiratory protection to avoid breathing vapors when

SAFETY DATA SHEET

Date Prepared : 11/28/2017
MSDS No : JSP-0290 Aerosol
Date Revised : 11/28/2017
Revision No : 12

STA'-PUT S200 Aerosol Adhesive

cover is removed. Ground and bond all equipment when handling flammable solvent-borne material.

STORAGE: Keep container closed when not in use. Store in a dry, well ventilated area, out of the sun and away from ignition sources. Do not remove or deface label. Prevent water or moist air from entering container.

STORAGE TEMPERATURE: 15.5°C (60°F) Minimum to 35°C (95°F) Maximum

SHELF LIFE: 1 year from manufacture date

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
EXPOSURE LIMITS				
Chemical Name	Type		ppm	mg/m ³
Methylene Chloride	OSHA PEL	TWA	25 ppm	NL
		STEL	125 ppm	NL
	ACGIH TLV	TWA	50 ppm	174 mg/m ³
		STEL	NL [1]	NL [1]
Hydrocarbon Propellant	OSHA PEL	TWA	1000 ppm	1800 mg/m ³
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	800 ppm	NL
		STEL	NL [1]	NL [1]

Footnotes:
1. NL = Not Listed

ENGINEERING CONTROLS: Provide sufficient explosion proof mechanical (general and/or local exhaust) ventilation to maintain exposure below the occupational exposure limit and exposure concentration.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields (or goggles) or a full face respirator.

SKIN: Wear chemical protective clothing & boots to prevent repeated or prolonged skin contact. Wear impervious gloves, if needed, to prevent repeated or prolonged skin contact.

RESPIRATORY: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

PROTECTIVE CLOTHING: Wear chemical resistant gloves, such as nitrile rubber.

WORK HYGIENIC PRACTICES: Use good hygiene practices when handling this material. Wash hands thoroughly after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

Date Prepared : 11/28/2017
MSDS No : JSP-0290 Aerosol
Date Revised : 11/28/2017
Revision No : 12

STA'-PUT S200 Aerosol Adhesive

PHYSICAL STATE: Aerosol

ODOR: Solvent-like

ODOR THRESHOLD: Not Determined

COLOR: Clear

pH: Not Determined

PERCENT VOLATILE: 84.9

Notes: by weight

FLASHPOINT AND METHOD: -104°C (-156°F)

FLAMMABLE LIMITS: 1.8 to 9.5

AUTOIGNITION TEMPERATURE: (788°F) to (1033°F)

VAPOR PRESSURE: Not Determined

VAPOR DENSITY: Not Determined

BOILING POINT: -24.4°C (-12°F) to -41.8°C (-43.2°F)

FREEZING POINT: Not Determined

MELTING POINT: Not Determined

POUR POINT: Not Determined

SOLUBILITY IN WATER: Slight

PARTITION COEFFICIENT: N-OCTANOL/WATER: Not Determined

EVAPORATION RATE: > 1.0 (n-Butyl Acetate=1)

DENSITY: 7.03 lbs/gal

PARTICLE SIZE: Not Determined

SPECIFIC GRAVITY: 0.843

MOLECULAR WEIGHT: Not Determined

(VOC): 433.5 gr/L EPA Method 24 VOC

Notes: Photochemically Reactive Only VOC: 295.3 gr/L

OXIDIZING PROPERTIES: Not Determined

COMMENTS: 3.30 lb VHAP/lb Solid
49.9% by weight HAP

10. STABILITY AND REACTIVITY

REACTIVITY: Yes

HAZARDOUS POLYMERIZATION: Product will not undergo polymerization.

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid fire, sparks, static electricity and hot surfaces.

POSSIBILITY OF HAZARDOUS REACTIONS: None Expected.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and carbon dioxide may form when heated to decomposition.

INCOMPATIBLE MATERIALS: Strong oxidizing agents, strong acids and strong bases.

SAFETY DATA SHEET

Date Prepared : 11/28/2017
MSDS No : JSP-0290 Aerosol
Date Revised : 11/28/2017
Revision No : 12

STA'-PUT S200 Aerosol Adhesive

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Methylene Chloride	985 to 1600 mg/kg	> 2000 mg/kg	52 mg/L (4-hr dose)
Hydrocarbon Propellant	No data	No data	No data

SERIOUS EYE DAMAGE/IRRITATION: Eyes, nose, throat, respiratory tract irritation.

GERM CELL MUTAGENICITY: Methylene chloride has been evaluated for its potential to induce genotoxic effects in both in vivo and in vitro systems with mixed results. Based on this evidence, methylene chloride exposure may be considered to be a weak mutagen in mammalian systems.

CARCINOGENICITY

Chemical Name	NTP Status	IARC Status	OSHA Status
Methylene Chloride	2	2B	X

IARC: Group 2B Animal Carcinogen

NTP: Animal Carcinogen

NOTES: This product contains methylene chloride, a chemical known to the State of California to cause cancer.

REPRODUCTIVE TOXICITY: Laboratory animal studies on mice, rats and rabbits have been conducted to evaluate the potential reproductive and developmental effects of methylene chloride exposures. Methylene chloride exposure has not been shown to cause teratogenic effects (birth defects) in experimental animals.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: This product contains components that will normally float on water. These components may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment.

ECOTOXICOLOGICAL INFORMATION: Contains components that are potentially toxic to freshwater and saltwater ecosystems.

BIOACCUMULATION/ACCUMULATION: Contains components with the potential to bio-accumulate.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Limited Quantity (Ltd Qty)

NAERG: 115

MARINE POLLUTANT #1: None

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION

SAFETY DATA SHEET

Date Prepared : 11/28/2017
 MSDS No : JSP-0290 Aerosol
 Date Revised : 11/28/2017
 Revision No : 12

STA'-PUT S200 Aerosol Adhesive

Limited Quantity (Ltd Qty)

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: Yes **PRESSURE GENERATING:** Yes **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt. %	CAS
Methylene Chloride	45 - 70	75-09-2

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt. %	CERCLA RQ
Methylene Chloride	45 - 70	2200 kg

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Methylene Chloride	75-09-2
Hydrocarbon Propellant	Mixture

CLEAN AIR ACT

Chemical Name	Wt. %	CAS
Methylene Chloride	45 - 70	75-09-2

STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
Methylene Chloride	New Jersey Right to Know List Pennsylvania Right to Know List Massachusetts Toxic Use Reduction Act (TURA) Reportable Chemical
Hydrocarbon Propellant	New Jersey Right to Know List Pennsylvania Right to Know List

CALIFORNIA PROPOSITION 65: This product contains methylene chloride, a chemical known to the state of California to cause cancer.

Chemical Name	Wt. %	Listed
Methylene Chloride	45 - 70	Cancer

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION



Flammable
Gas



Compressed
Gas



Poison

SAFETY DATA SHEET

Date Prepared : 11/28/2017
MSDS No : JSP-0290 Aerosol
Date Revised : 11/28/2017
Revision No : 12

STA'-PUT S200 Aerosol Adhesive

16. OTHER INFORMATION

Date Revised: 11/28/2017


INFORMATION CONTACT: (781) 878-7015

REVISION SUMMARY: This MSDS replaces the 11/10/2014 MSDS. Revised: **Section 1:** Date Issued.

HMIS RATING

HEALTH	*	2
FLAMMABILITY		4
PHYSICAL HAZARD		0
PERSONAL PROTECTION		B

NFPA CODES



GENERAL STATEMENTS: Keep out of reach of children
For professional or industrial use only

MANUFACTURER DISCLAIMER: This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his/her evaluation of the product's hazards and safety precautions to be taken in its use. The data in this SDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW Polymers Sealants North America. The data on this sheet relates only to the specific material designated herein. ITW Polymers Sealants North America assumes no legal responsibility for use or reliance upon these data.