Date Prepared: 08/10/2018

MSDS No : ST102

Date Revised : 08/10/2018

Revision No: 7

STA'-PUT ST102 Solvent Cleaner

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: STA'-PUT ST102 Solvent Cleaner

MANUFACTURER

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300

ITW Polymers Sealants North America 56 Air Station Industrial Park Rockland, MA 02370

Product Stewardship: (781) 878-7015

COMMENTS: STA'-PUT is a registered trademark of Illinois Tool Works, Inc.

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Irritation, Category 2
Eye Irritation, Category 2A
Reproductive Toxicity, Category 2
Target Organ Toxicity (Single exposure), Category 3
Target Organ Toxicity (Repeated exposure), Category 2
Aspiration Hazard, Category 1

Environmental:

Acute Hazards to the Aquatic Environment, Category 2 Chronic Hazards to the Aquatic Environment, Category 3

Physical:

Flammable Liquids, Category 2

GHS LABEL



Flame



Exclamation mark



Health hazard



Environment

SIGNAL WORD: DANGER HAZARD STATEMENTS

H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eve irritation.

H336: May cause drowsiness or dizziness.

H361: Suspected of damaging fertility or the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

H401: Toxic to aquatic life.

H412: Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENT(S)

Date Prepared : 08/10/2018 **MSDS No :** ST102 **Date Revised :** 08/10/2018

Revision No: 7

STA'-PUT ST102 Solvent Cleaner

Prevention:

[201]: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

P240: Ground and bond container and receiving equipment.

P241: Use explosion-proof [electrical/ventilating/lighting] equipment.

P242: Use non-sparking tools.

P243: Take action to prevent static discharges.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313: IF exposed or concerned: Get medical advice/ attention.

P321: Specific treatment is required.

P331: Do NOT induce vomiting.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P362: Take off contaminated clothing.

P370+P378: In case of fire: Use appropriate media to extinguish.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container according to local, regional, national, and international regulations.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: DANGER! Flammable liquid and vapor. Vapor may cause flash fire. Harmful or fatal if swallowed. Harmful if absorbed through the skin. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage. High vapor concentrations may cause drowsiness. Can cause eye, skin and respiratory tract irritation.

POTENTIAL HEALTH EFFECTS

EYES: Mildly irritating to the eyes.

SKIN: May cause moderate skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

SKIN ABSORPTION: May be absorbed through the skin in harmful amounts.

INGESTION: Harmful or fatal if swallowed. Pulmonary aspiration hazard. While ingesting or vomiting, may enter lungs and produce damage. May produce central nervous system effects, which includes dizziness, loss of balance and coordination, unconsciousness, coma and even death. Irritating to mouth, throat, and stomach.

INHALATION: Can cause severe central nervous system depression (including unconsciousness). May cause

Date Prepared: 08/10/2018 **MSDS No**: ST102 **Date Revised**: 08/10/2018

Revision No: 7

STA'-PUT ST102 Solvent Cleaner

headaches and dizziness. Vapors irritating to eyes and respiratory tract. Prolonged or repeated exposure may cause liver and kidney damage. Solvent "huffing/sniffing" abuse or intentional prolonged overexposure to high levels of vapors can produce abnormal behavior, convulsions, hallucinations, delirium, nervous system damage, serious disturbances of heart rhythm and sudden death.

ROUTES OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, and Skin Contact

TARGET ORGAN STATEMENT: Central Nervous System (CNS) **IRRITANCY:** Eyes, nose, throat, respiratory tract, and skin irritation.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Toluene	~ 100	108-88-3

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of tempered water (at least 15-20 minutes) lifting upper and lower eye lids occasionally. Get immediate medical attention.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: Small amounts are not expected to produce adverse health effects. Larger amounts should be recovered by aspiration. Get medical attention.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Slight irritation.

SKIN: Substance causes moderate skin irritation.

SKIN ABSORPTION: Skin absorption of material may produce systemic toxicity.

INGESTION: Toxic and is harmful if swallowed; may produce (specific organ) damage.

INHALATION: Exposure to high concentrations of vapor or mist can cause central nervous system depression with symptoms of headache, dizziness, stupor, loss of consciousness or death depending on concentration and duration of exposure. Exposure to high concentrations can cause irregular heartbeat, cardiac arrest and death. Overexposure has been shown to cause adverse effects on the lungs, liver, kidney, nervous system and internal organs.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Class IB

GENERAL HAZARD: Flammable liquid and vapor.

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical or foam.

EXPLOSION HAZARDS: Avoid fire, sparks, static electricity and hot surfaces. Liquid readily evaporates at room/ambient temperature. Vapors are invisible, flammable, heavier than air, and may accumulate in low areas and spread long distances. Distant ignition and flashback are possible.

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus with pressure-demand, full face piece SCBA (MSHA/NIOSH approved or equivalent) and full protective gear.

SENSITIVE TO STATIC DISCHARGE: Not Applicable

Date Prepared: 08/10/2018 MSDS No: ST102 Date Revised: 08/10/2018

Revision No: 7

STA'-PUT ST102 Solvent Cleaner

SENSITIVITY TO IMPACT: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide and Carbon Dioxide may form when heated to decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitible vapors, have been removed, thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.

LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof mechanical means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. Flammable vapors may cause flash fire or ignite explosively. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near container. Do not cut, drill, grind, or expose containers to heat, sparks, static electricity or other source of ignition. Explosion may occur causing injury or death.

HANDLING: Containers should be tightly closed to prevent contamination with foreign materials and moisture. Employee education and training in the safe handling of this product are required under the Federal OSHA Hazard Communication Standard.

STORAGE: Keep container closed when not in use. Store in a dry well ventilated area and out of the sun.

STORAGE TEMPERATURE: 15.5°C (60°F) Minimum to 35°C (95°F) Maximum

SHELF LIFE: 1 year from manufacture date

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Date Prepared: 08/10/2018

MSDS No: ST102 Date Revised: 08/10/2018

Revision No: 7

STA'-PUT ST102 Solvent Cleaner

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
	EXPOSURE LIMITS			
Chemical Name	Type ppm mg/m³			
	OCHA DEI	TWA	200 ppm	NL
Toluene	OSHA PEL	STEL	300 ppm ^[1]	NL [1]
	ACCTU TUV	TWA	20 ppm	NL
	ACGIH TLV	STEL	NL ^[2]	NL [2]

Footnotes:

- 1. C = Ceiling
- 2. NL = Not Listed

ENGINEERING CONTROLS: Provide sufficient explosion proof mechanical (general and/or local exhaust) ventilation to maintain exposure below the occupational exposure limit and exposure concentration. Use only in a well ventilated area. Ground and bond all equipment.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields. A face shield may be necessary if spraying the product. **SKIN:** Wear impervious gloves, if needed, to prevent repeated or prolonged skin contact.

RESPIRATORY: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

WORK HYGIENIC PRACTICES: Use good hygiene practices when handling this material. Wash hands thoroughly after use.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Solvent-like

ODOR THRESHOLD: Not Determined

COLOR: Clear

pH: Not Determined

PERCENT VOLATILE: 100

FLASHPOINT AND METHOD: 8.9°C (48°F)

FLAMMABLE LIMITS: 1.2 to 7.1

AUTOIGNITION TEMPERATURE: (99.7°F)

VAPOR PRESSURE: Not Determined

Date Prepared: 08/10/2018 MSDS No: ST102 Date Revised: 08/10/2018

Revision No: 7

STA'-PUT ST102 Solvent Cleaner

VAPOR DENSITY: Not Determined BOILING POINT: 110.6°C (231°F) FREEZING POINT: Not Determined MELTING POINT: Not Determined POUR POINT: Not Determined SOLUBILITY IN WATER: Soluble

PARTITION COEFFICIENT: N-OCTANOL/WATER: Not Determined

EVAPORATION RATE: > 1 (n-Butyl Acetate=1)

DENSITY: 7.25 lbs/gal

PARTICLE SIZE: Not Determined **SPECIFIC GRAVITY:** 0.869

VISCOSITY: Not Determined

MOLECULAR WEIGHT: Not Determined **(VOC):** 869 gr/L EPA Method 24 VOC

Notes: Photochemically Reactive Only VOC: 869.0 gr/L

OXIDIZING PROPERTIES: Not Determined

COMMENTS: 0 lb VHAP/lb Solid

0% by weight HAP

10. STABILITY AND REACTIVITY

REACTIVITY: Yes

HAZARDOUS POLYMERIZATION: Product will not undergo polymerization.

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid fire, sparks, static electricity and hot surfaces.

POSSIBILITY OF HAZARDOUS REACTIONS: None Expected.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and carbon dioxide may form when heated to

decomposition.

INCOMPATIBLE MATERIALS: Oxidizing materials

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Toluene	2600 to 7500 mg/kg	12124 mg/kg	8000 ppm (4-hr dose)

SERIOUS EYE DAMAGE/IRRITATION: Slight eyes and skin irritation.

CARCINOGENICITY

Chemical Name	IARC Status
Toluene	3

Date Prepared: 08/10/2018

MSDS No: ST102 Date Revised: 08/10/2018

Revision No: 7

STA'-PUT ST102 Solvent Cleaner

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: This product contains components that may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment.

ECOTOXICOLOGICAL INFORMATION: Contains components that are potentially toxic to freshwater and saltwater ecosystems.

BIOACCUMULATION/ACCUMULATION: Contains components with the potential to bio-accumulate.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Toluene

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: 1294
PACKING GROUP: II

NAERG: 130

MARINE POLLUTANT #1: None

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: Yes PRESSURE GENERATING: No REACTIVITY: No ACUTE: Yes CHRONIC: Yes

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
Toluene	~ 100	108-88-3

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Toluene	~ 100	1,000 lbs.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Date Prepared: 08/10/2018

MSDS No: ST102 Date Revised: 08/10/2018

Revision No: 7

STA'-PUT ST102 Solvent Cleaner

Chemical Name	CAS
Toluene	108-88-3

CLEAN AIR ACT

Chemical Name	Wt.%	CAS
Toluene	~ 100	108-88-3

STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
Toluene	New Jersey Right to Know List Pennsylvania Right to Know List Massachusetts Toxic Use Reduction Act (TURA) Reportable Chemical

CALIFORNIA PROPOSITION 65: This product contains toluene, a chemical known to the state of California to cause birth defects or other reproductive harm.

Chemical Name	Wt.%	Listed
Toluene	~ 100	Developmental Toxicity

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION







IOXIC

16. OTHER INFORMATION

Date Revised: 08/10/2018

INFORMATION CONTACT: (781) 878-7015

REVISION SUMMARY: This MSDS replaces the 11/28/2017 MSDS. Revised: **Section 1:** Date Issued. **Section**

14: DOT (DEPARTMENT OF TRANSPORTATION) - PACKING GROUP.

HMIS RATING

111120 10112110	
HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	В

NFPA CODES 3 2 0

GENERAL STATEMENTS: Keep out of reach of children

For professional or industrial use only

MANUFACTURER DISCLAIMER: This document may be used to comply with OSHA's Hazardous Communication

Date Prepared: 08/10/2018 MSDS No: ST102 Date Revised: 08/10/2018

Revision No: 7

STA'-PUT ST102 Solvent Cleaner

Standard, 29 CFR 1910.1200.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his/her evaluation of the product's hazards and safety precautions to be taken in its use. The data in this SDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW Polymers Sealants North America. The data on this sheet relates only to the specific material designated herein. ITW Polymers Sealants North America assumes no legal responsibility for use or reliance upon these data.